

Bondi

600mm Double Diffused/Wireguard Emergency Batten

The Bondi series LED batten lights are the perfect solution for projects and economic applications, utilising a replaceable Kwicky module for unparalleled ease of maintenance. Optional Beacon Bondi motion sensor available for a range of lighting-control and energy-saving applications.



Features

- 2,000 Lumens
- Tri-Colour
- LiFePO₄ Lithium Battery
- Kwicky Replaceable Emergency Module

Accessories

- Replacement Kwicky: EMP-KWICKY-EM
- Motion Sensor: SENSOR-BONDI
- Wireless Motion Sensor: BEACON-BONDI
- Replacement Diffuser: DIFF-600-BONDI
- Replacement Wireguard: WIRE-600-BONDI

	emergency	self-test	networking
ORDER CODE	BONDI-600-2-W-EM BONDI-600-2-D-EM	BONDI-600-2-W-ST BONDI-600-2-D-ST	BONDI-600-2-W-LR BONDI-600-2-D-LR
WARRANTY	3 Years	5 Years	5 Years
TRADITIONAL DROP TEST			
APP SCHEDULED TESTING			
REMOTE SCHEDULED TESTING			



Download the Elumen app



elumen.com.au
1300 927 533

Device Specifications

OPERATIONAL INFORMATION	
VOLTAGE	220 - 240VAC
FREQUENCY	50Hz
LUMINOUS FLUX	2000lm (Wireguard) 1950lm (Diffused)
POWER CONSUMPTION	22W
AMBIENT TEMPERATURE	1°C - 40°C
IP RATING	IP20
COLOUR TEMPERATURE	3000K / 4000K / 5000K
MOUNTING TYPE	Surface Ceiling
OPERATING MODE	Switch Controlled, Maintained, Non-Maintained
PROJECTED LED LIGHT SOURCE LIFE	100,000 Hours

CONSTRUCTION, DIMENSIONS AND WEIGHT	
CONSTRUCTION	White Powder Coated Steel Body, Polycarbonate Diffuser
WEIGHT	1.95kg
CARTON QTY	4
CARTON DIMENSIONS	640mm x 280mm x 220mm
CARTON WEIGHT	8.5kg

COMPLIANCE AND TESTING		
STANDARDS	AS/NZS 2293.3	
	AS/NZS 60598.2.22	
	AS/NZS CISPR 15	
EMERGENCY CLASSIFICATION	Diffuser:	Wireguard:
	- C0: D63	- C0: D63
	- C90: D12.5	- C90: D16

Product Drawing

